

#### Features :

- 600A
- AC/DC V, AC A
- Continuity, Diode
- Data Hold, Auto Power OFF
- Jaw Diameter 30mm
- Low Battery indication
- Double Insulation Protection Class II



#### Technical Specifications :

Model	Metrix+ 125A
LCD Display	3 <sup>1</sup> / <sub>2</sub> Digit, 1999 Count
Safety Standard	IEC 1010-1
Range	Manual
DC Voltage	600V $\pm$ (0.8% $\pm$ 5d)
AC Voltage	600V $\pm$ (1.2% $\pm$ 5d)
AC Ampere	2000m/20/200/600A $\pm$ (2% $\pm$ 10d)
Resistance	2000 $\Omega$ $\pm$ (1% $\pm$ 5d)
Jaw Diameter	30mm
Other Functionalities	Continuity, Diode, Data Hold, Auto Power OFF, Auto Negative Polarity Indication "-", Low Battery Indication, Overload Protection
Storage Temperature & Humidity	-20°C ~ 60°C, $\leq$ 80% RH
Operating Temperature & Humidity	0°C ~ 40°C, $\leq$ 70% RH
Battery	AAA 1.5V x 2
Dimension & Weight	165x68x28mm, 180g(including battery)
Accessories Included	Instruction Manual, Test Lead, Carry Case, Battery